Distoration Rate For Pre Print Plates For .107 Is 96.81%

Distoration Rate For Tail Print Plates For .067 Is 98.06% 1 Duro Way
Walton, KY 41094
Duro.ArtDepartment@novolex.com

Starting Web: 30 3/4" Finished Web 30 1/2"

CREATED BY: B. Wallrawe

DESIGN GROUP: Shopper Series

JV Slit Kary 9 x 5 3/4 x 13 3/4

DATE: 2/10/16 SCALE: FULL

Printed Flap 7 1/8"

PLEASE NOTE: This proof is for copy, content, and position approval only. This proof is not for actual color or paper substrate used to produce your order.

Carefully check all traps (overlap of color) punctuation, spelling, copy and elements. Please use attached approval letter for signed approval. Approval letter, proof and interest outs must be returned to produce your order.

Because Of Machine Movement In Bag Conversion, Copy Should Be Placed At Least 1/4" From Fold Lines Or Edges. In The Top Area, Use 1/2" Bleed. Border Designs Should Be Kept 1/2" From Fold Edges, Top Cutoff And Bottom Fold. Full Panel Print Must Bleed Into Top & Bottom Of Bag. Which Is Indicaated On Template ink roll outs must be returned to produce your order.

BORDER DESIGNS

Fill All 5 Anti-Bounce Area With 40% Screen In All Colors Containing Screens

Fold And Paste Lines

Bleed Copy Must Any Copy Above This Extend To this Line. Line Will Not Be Seen. Final Art For Gusset 5 3/4" Face 9.00" Gusset 5 3/4" Face 9.00" Plates Should Stop Back Fold Line. AFTER CONVERSION, THIS AREA (.25") WILL APPEAR IN BOTTOM OF BAG CUTOFF – Slit Top 4.25"– - Slit Top 4.25"-UNPRINTED PASTE AREA UNPRINTED PASTE AREA PLACEMENT OF DENSITY BARS Cut Flap 6 1/8" (UP TO 6 COLORS)